

TWISTER

T2

#1 Trimming System Among Commercial Producers

| T2 | Type | Feed (lbs/hr) | Feed (kg/hr) |
|----|------------|------------------|-----------------|
| 1 | Wet | Up to 35 | Up to 16 |
| 2 | Wet | Up to 78 | Up to 36 |
| 3 | Wet | Up to 124 | Up to 56 |
| 4 | Wet | Up to 172 | Up to 78 |
| 1 | Dry | Up to 11 | Up to 5 |
| 2 | Dry | Up to 25 | Up to 12 |



T2 Trimmer Features

- Large-Commercial Scale
- Harvest size: ~100+lbs
- Start with Tandem scale up to Triple
- Continuous flow and runtime
- 304 stainless steel tumbler to mitigate risk of contamination
- Nitrided steel blades increase strength and resistance and decrease buildup
- Minimal handling >1 min in tumbler
- Watertight electrical and motors allow for a complete high-pressure washdown
- Wheels allow for easy transport whether indoor or outdoor



TWISTER

T2



Extension C



TESTED

SPECIFICATIONS

| | |
|----------------------------|------------------|
| Product Number | 02-10006B |
| Input Voltage | 120V, 60 Hz |
| Current Draw | 15.5A |
| Blade Motor | 1HP |
| Tumbler Diameter | 6in / 10.1cm |
| Tumbler Slots | 50 x .25in/.3cm |
| Cut Height | .040in / 1mm |
| Weight | 215lbs /97.5kg |
| Shipping Weight (w/ T2-LC) | 420lbs / 190kg |
| Length | 42.5in / 107.9cm |
| Width | 27.5in / 69.9cm |
| Height | 32.5in / 82cm |
| Circuit Breaker Required | 20A / 120V |
| Connector (plug) | NEMA 5-20P |
| Certifications | CSA, UL |

ACCESSORIES & COMPONENTS

| | |
|-----------------------------|--------------|
| T2 Leaf Collector | 23-0117-00-P |
| T2 Trim Saver | 23-0200-01-P |
| T2 Rail (Single) | 24-0400-00-P |
| T2 Rail Extension | 24-0401-01-P |
| Feed Conveyor (Inbound) | 26-0001-02 |
| Quality Conveyor (Outbound) | 26-0002-02 |

ADDITIONAL REQUIREMENTS

12 AWG (Minimum AWG Size)

7.6m / 25ft max length

CONNECTOR (PLUG)

NEMA 5-20P



Visit twistertrimmer.com or call your Twister Rep for an extensive list of replacement parts or accessories.

